



Product Features

- Compact and lightweight design, easy to carry
- 7.4V, 2600mAh large capacity battery
- Supports multiple barcode printing
- One-touch cover opening, OLED display
- Automatic sleep/automatic wake-up

Application



Parking ticket



Ship transportation



Property bill



On-site repair /installation



Warehousing & Logistics

Product model		APMP-112-440-SUB	
Printing	Print mode	Direct Thermal	
	Print width	104 mm	
	Print resolution	203dpi(832dots/line)	
	Print speed max.	70mm/s	
Paper	Type	Thermal receipt	
	Width	34-112 mm	
	Roll paper diameter (O.D)	50mm	
	Thickness	0.055-0.09mm	
Character set	Font	ASC II :9x17,9x24,16x18,12x24, GBK:24x24	
	Code page	48	
Sensor		Paper end, Platen in position sensor	
Interface	Standard	Bluetooth/dual mode, Bluetooth+USB	
	Optional	WIFI/4G(Customization)	
Barcode	1D barcode	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93	
Emulation	2D barcode	QR Code,PDF 417	
	Compatible	ESC/POS	
Software	Driver	Windows Driver, Linux Driver	
	SDK	Windows SDK, Linux SDK, Android SDK	
Battery charger Battery	AC/DC	5V, 2A	
		7.4V Li-ion, 2600mAh, 4.0Hrs Charging time	
Reliability	TPH life	50km	
	Pulse Activation	100 Million pulse	
Physical	Dimensions (WxLxH)mm	148x108x55.7mm	
	Weight	530g(with battery)	
Environment	Temperature	Operating:0°C~50°C	Storage:-20°C ~ 60°C
	Humidity(No condensation)	Operating:10%RH~80%RH	Storage:10%~90%RH