



## ■ Product Features

- Lightweight design, easy to carry
- Multiple interfaces available
- Head piece overheat protection, paper shortage detection
- Auto sleep/auto wake-up
- Support multiple languages

## ■ Application



Parking ticket



Ship transportation



Property bill



On-site repair /installation



Warehousing & Logistics

product model		APMP-58-240-BU
Printing	Print mode	Direct Thermal
	Print width	48 mm
	Print resolution	203dpi(384dots/line)
	Print speed max.	70 mm/s
Paper	Type	Thermal paper
	Width	58 mm
	Roll paper diameter (O.D)	40 mm
	Thickness	0.055-0.09mm
Character set	Font	Font A:12x24; Font B:9x17 GBK:24x24
	Code page	48
Sensor		Printer head overheat, Paper end
Interface	Standard	Bluetooth+USB
	Optional	-
Barcode	1D barcode	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D barcode	QR Code
Emulation	Compatible	ESC/POS
Software	Driver	Windows Driver, Linux Driver, OPOS Driver
	SDK	Windows SDK, Android SDK, IOS SDK
Battery charger	AC/DC	5V, 1A
Battery		2600mAh 3.7V rechargeable Lithium battery 4.0Hrs Charging time
Reliability	TPH life	50km
	Pulse Activation	100 Million pulse
Physical	Dimensions (WxLxH)mm	119.3*81.5*47mm
	Weight	199g(with battery)
Environment	Temperature	Operating:0°C~50°C      Storage:-20°C ~ 60°C
	Humidity(No condensation)	Operating:10%RH~80%RH      Storage:10%~90%RH