



■ Product Features

- Lightweight design, easy to carry
- One-touch opening: OLED screen status display
- Waterproof and dustproof rating reaches IP54, can still work outdoors on rainy days
- Multiple interfaces available
- Automatic sleep/automatic wake-up
- Supports multiple barcode printing

■ Application



Parking ticket



Ship transportation



Property bill



On-site repair /installation



Warehousing & Logistics

product model		APMP-80 340-SUB
Printing	Print mode	Direct Thermal
	Print width	72 mm
	Print resolution	203dpi(384dots/line)
	Print speed max.	90 mm/s
Paper	Type	Thermal paper
	Width	80 mm
	Roll paper diameter (O.D)	40 mm
	Thickness	0.055-0.09mm
Character set	Font	Font A:12x24; Font B:9x17 GBK:24x24
	Code page	48
Sensor		Paper end
Interface	Standard	Bluetooth+USB
	Optional	WIFI,RS232C
Barcode	1D barcode	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D barcode	QR Code, PDF 417
Emulation	Compatible	ESC/POS
Software	Driver	Windows Driver, Linux Driver, OPOS Driver
	SDK	Windows SDK, Android SDK, IOS SDK
Battery charger Battery	AC/DC	5V, 1A
		7.4V Li-ion, 1500mAh/2000mAh 3.0/3.5Hrs Charging time
Reliability	TPH life	50km
	Pulse Activation	100 Million pulse
Physical	Dimensions (WxLxH)mm	111x124x48mm
	Weight	360g(with battery)
Environment	Temperature	Operating:0°C~50°C Storage:-20°C ~ 60°C
	Humidity(No condensation)	Operating:10%RH~80%RH Storage:10%~90%RH